

SAMPLING TAPES FOR RESTRICTED TANK APPLICATIONS



Nothing but the best.

MMC S (697)



SAMPLING TAPES

Reel Crank

Tape

Tape Reel Lock

Read Tape Here

Grounding Lug

Securing Collar

Tape Wiper Assembly

Replaceable Barrel Securing Nuts

Restricted Barrel for

Restricted Barrel for

Securing Collar

and 3" Mini "S" Valves

1/3 and 1/2 Liter Sampling

1 Liter Sampling via 4""S"

PRODUCT CODE: (typical)

"18" (1/2 liter) -

"18M" (1/3 liter)

"F50" and "C50" (1/2 liter)

Tane Seal

REAR VIEW with "S" Valve Barrel

9 (229mm) -

23 3/4

(603mm)

(152mm)

2326R 2562-10018

Model No. 2326R2562-100S9

FRONT VIEW with 1/2 liter

No. 2326R2562-10018

sampler extended tube Model

8

20 3/8

(518mm)

+24 7/8

(632mm)

725 1/2 (648mm)

MMC manufactures three sampling tapes for use with its range of vapor control valves. The model 2326R2562-100S9 is used with 4-inch "S" valves and 3-inch Mini "S" valves. The model 2326R2562-10018 is used with "A," "B," Micro "B" (MB), "U" and "U/B" valves. The model 2326R2562-10018M is used for the 1-1/2 inch Mini Micro "B" (MMB) and C38 valves. Each Flexi-Dip sampling system comes complete with tape, snap hook, specified sampler, brass sounding bob and appropriate vapor valve storage tube.

MMC manufactures a complete line of stainless steel zone samplers. Our model 1LTR-3.5X10LG is 1 liter and for use with 4-inch "S" valves. The 1LTR-2.5X16LG sampler is for the 3-inch Mini "S" valve. Also available are two 1/2-liter models: 1/2LTR-1.625X18 for "A" "B" "MB" F50, C50, "U" and "UB" valves, and 1/3LTR-1.375X18 for "MMB" and C38 valves.

MMC also manufactures a complete line of bottom samplers.

SPECIFICATIONS

ACCURACY OF TAPE READING:

+/- 1/8 inch (+/- 3mm)

APPLICATION:

R - Restricted sampling (1/3, 1/2 and 1 liter) through MMC vapor control valve (see below)

TAPE LENGTHS:

Dual marked 100ft/30m, 120ft/37m

TYPICAL WEIGHTS W/O SAMPLER:

(reel, frame, tape, etc.)

100ft/30m for 1 liter sampling

9 lbs (4.1 kg)

100ft/30m for 1/2 liter sampling

10 lbs (4.5 kg) w/o adaptor

SAMPLERS:

MMC International Corp.

All stainless steel construction as standard (brass optional)

1 liter - 3.5 x 10 lg; 1 liter - 3.5 O.D. x 10 lg - 4-inch "3" valve

1 liter - 2.5 x 16 lg: 1 liter - 2.5 O.D. x 16 lg - 3-inch Mini "S" valve

1/2 liter - 1.625 x 18; 1/2 liter - 1.625 O.D. x 18 lg - "A," "B," "U," Micro "B," F50 and C50 valves

1/3 liter - 1.375 x 18; 1/3 liter - 1.375 O.D. x 18 lg -Mini-Micro *B" and C38 1-1/2-inch valves



37 7/8

(962mm)

Россия, 121357, Москва, ул. Инициативная, дом 7, кор. 3, пом. IV, ком. 1-9

Тел: +7 (499) 990-05-50; +7 (800) 775-29-59