

## MODLINK MSDD DATA INSERT

1×SUB-D9 female/female + 1×RJ45

RJ45; SUB-D9

1 × RJ45, 8-pole metal, CAT5e (female/female)

1 × SUB-D9 (female/female)

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### Approvals



#### General data

Dimensions H × W × D 88×51×21 mm

#### SUB-D9

Operating voltage 48 V AC/DC

Operating voltage (UL Rating) max. 30 V AC/42.4 V DC

Operating current 3 A

Operating current (UL Rating) max. 175 mA

No. of poles 9-pole

Connection front side SUB-D (female)

Connection rear side SUB-D (female)

Locking of ports UNC 4...40 bolt

**RJ45**

Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current (UL Rating)	max. 175 mA
Connection front side	RJ45
Connection rear side	RJ45
Locking of ports	Snap In
Specification	CAT5e, class D, 100 MHz, (EN 50173-1)

**Shielding plate**

Connection	T threaded hole M4
Tightening torque	0.9 Nm $\pm$ 0.1

**Commercial data**

country of origin	DE
customs tariff number	85366990
EAN	4048879037563
eClass	27144001
minimum order quantity	1