

EXACT8, 10XM8, 3 POLE PRE-WIRED CABLE



10.0m PUR/PVC 10*0,34+2*0,75

10-way, 3-pole
PUR/PVC
10.0 m



Further cable lengths on request. Plastic housings with good resistance against chemicals and oils. The resistance to aggressive media should be individually tested for your application. Further details on request.

[Link to Product](#)


Illustration



M8-Females 3-pole



for 1 signal per port



Product may differ from Image

Approvals



Technical Data

Operating voltage	24 V DC
Operating current per contact	max. 2 A
Signal per port	1 - (31-32)
Protection	IP65/IP67
Housing	Plastic, flame retardant
Total current	max. 8 A
Locking of ports	Screw thread M8 × 1 mm

Cables

Cable number	385
No./diameter of wires	10×0.34 + 2×0.75 mm ²
Wire isolation	PVC (br, bl, wh, gn, pk, ye, bk, gr, rd, vi, grpk, rdbl)
C-track properties	2 Mio.
Jacket Color	gray

Shore hardness outer jacket	85 ± 5A
Material (jacket)	PUR/PVC (UL/CSA)
Outer diameter	approx. 8.3 mm
Bend radius (fixed)	5 × outer Ø
Bend radius (moving)	10 × outer Ø
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+60 °C

General data

Temperature range	-20...+80 °C, depending on cable quality
-------------------	--

Contact layout

Contact 1	(+)
Contact 3	(-)
Contact 4	(NO)/(S1)
LED display	LED (green): Power / LED (yellow): (S1)

Commercial data

country of origin	DE
customs tariff number	85444290
minimum order quantity	1